



New Features

- ✓ USB connectivity to PC
- ✓ ToolKit configuration support
- ✓ Password protection to all variants
- ✓ Same look & feel as SPM-D
- ✓ Drop-In replacement

Synchronizers for 2/3-phase AC Gen-Sets

DESCRIPTION

Woodward understands the time-intensive nature of Power Generation projects. Ensuring the longevity of components is one way we can make our customers successful. Woodward has supplied and supported the well-established SPM-D line of synchronizers for 20+ years. With the state of the art Drop-In replacement successor, SPM-D2 the life of this synchronizer line is now extended. All of the SPM-D2 synchronizers are password protected and are configurable either through HMI as before or through ToolKit configuration tool with USB connectivity.

The SPM-D2-10 series are microprocessor-based synchronizers designed for use on two or three phase AC generators equipped with Woodward or other compatible speed controls and automatic voltage regulators. The SPM-D2-10 synchronizers provide automatic frequency, phase and voltage matching using either analog- or discrete output bias signals. These synchronizers are applied to a wide range of prime movers and generators, as its control signals may be set to fit several types of gensets - from fast reacting diesel engines to soft reacting gas turbines.

The SPM-D2-10 synchronizers are available in 3 base models:

- **SPM-D2-10 ...** : provides 1-phase / 2-wire voltage measurement with options for analog and/or discrete biasing signals and wide range power supply
- **SPM-D2-10 .../YB**: provides 3-phase / 4-wire voltage measurement with discrete biasing signals and option for wide range power supply
- **SPM-D2-10 .../PSY5**: provides 1-phase / 2-wire voltage measurement with discrete biasing signals, option for wide range power supply and 2 sets of switchable parameter set.

FEATURES


- Phase match or slip frequency synchronization with voltage matching
- Two-Phase or three-phase true RMS voltage sensing of generator and bus with Class I accuracy
- Selectable operating modes like SPM-A (Run, Check, Permissive and Off)
- Synch-Check and synchronization time monitoring
- Dead bus closing of CB on demand
- 2 setting blocks, each containing 7 configurable parameters (in PSY5 variants) selectable through DI: Frequency/Voltage control dead-band, Frequency/Voltage control time pulse, Frequency/Voltage control gain, Circuit breaker time compensation
- Control outputs: Discrete raise/lower for speed and voltage in all variants, | X and XN variants: also configurable analog signals (Voltage, Current and PWM)
- Voltage and frequency control in isolated operation
- Two line bright liquid crystal display for operation, alarm, measuring values visualization and parametrization
- Front face with synchronoscope and indication of breaker state/control activity
- Multi-level password protection of parameters
- Woodward ToolKit™ software for configuration via USB
- Two built-in languages: English, German

- Synchronization for one or two circuit breakers
- Frequency, Phase and Voltage Matching
- Selectable control outputs for speed and voltage biasing
- Compatible with a wide range of GOVs and AVR
- Circuit breaker time compensation
- Two lines bright LCD display for generator and bus values
- Front face synchronoscope for easy commissioning
- True RMS measurement for reliable operation
- Configurable through HMI or PC
- Wide range power supply available
- Switchable parameter sets available
- CE Marked (RoHS 2 compliant)
- UL/cUL Listed

SPECIFICATIONS


Power supply		isolated
[Standard].....	12/24 V _{DC} (9.5 to 32 V _{DC})	.AgCdO
[N, XN and NYB Packages]	90 to 250Vac / 120 to 375 Vdc;	DC: 2.00 A _{AC} @250 V _{AC}
.....	100 to 240 Vac -15%/+10% (UL rating only)	DC: 0.36 A _{DC} @125 V _{DC} / 0.18 A _{DC} @250 V _{DC}
Intrinsic consumption	max. 10 W	Pilot Duty (PD) AC: B300
Ambient temperature (operation).....	-20 to 70 °C	DC: 1.00 A _{DC} @24 V _{DC} / 0.22 A _{DC} @125 V _{DC} / 0.10 A _{DC} @250 V _{DC}
[N, XN and NYB Packages]	-20 to 60 °C	Analog Outputs (isolated) freely scalable
Ambient temperature (storage).....	-30 to 80 °C	Type ± 10 V / ± 20 mA / PWM
Ambient humidity.....	95%, non-condensing	Insulation voltage (continuously, AVR out)..... 300 V _{AC}
Voltage (λ/Δ)		Insulation voltage (continuously, Gov out)..... 100 V _{AC}
[1] 100 Vac Rated (V _{rated}).....	66/15 V _{AC}	Resolution 12 Bit
Max. value (V _{max}).....	150 V _{AC}	± 10 V (scalable) internal resistance 500 Ohms
or [4] 400 Vac Rated (V _{rated}).....	230/400 V _{AC}	± 20 mA (scalable) maximum load 500 Ohms
Max. value (V _{max}).....	300 V _{AC}	Housing Front panel flush mounting Type APRANORM DIN 43 700
Rated surge volt. (V _{surge}).....	[1] 2.5kV, [4] 4.0 kV	Dimensions WxHxD 144 × 72 × 122 mm
Accuracy Class 1		Front cutout WxH 138 [+1.0] × 68 [+0.7] mm
Measuring frequency.....	50/60 Hz (40 to 70 Hz)	Connection (screw/plug terminals depending on connector) .. 1.5 mm ² or 2.5 mm ²
Linear measuring range.....	1.3 x V _{rated}	Front insulating surface
Input resistance.....	[1] 0.21 MΩ, [4] 0.696 MΩ	Protection System / Sealing.....
Current Rated (I _{rated}).....	[1] .../1A, [5] ... /5A	Front IP42 with correct installation
Linear measuring range.....	3.0 x I _{rated}	Front IP54 (with gasket P/N 8923-1037)
Burden.....	< 0.15 VA	Back IP20
Rated short-time overcurrent (1 s).....	[1] 50 x I _{rated} , [5] 10 x I _{rated}	Weight approx. 800 g
Discrete inputs	isolated	Listings tested according to applicable IEC standards
Input range.....	12/24 V _{DC} or 18 to 250 Vac/dc CE, UL/cUL listing for ordinary locations
Input resistance.....	approx. 6.8 kΩ or 68 kΩ	Marine (Pending) LR (Type Approval), ABS (Type Approval)

DIMENSIONS



TERMINAL DIAGRAM

NOTE The terminals used for connection depend on the implemented functionality of each package. The drawing below gives an overview with sample package **XN** – for details please see the dedicated Technical Manual listed in the features table at the rear page.



RELATED PRODUCTS

- Load Share Synchronizer **SPM-D2-11** (Product Specification # 37623)
- Digital Synchronizer and Load Control **DSLC-2** (Product Specification # 37493)
- Master Synchronizer and Load Control **MSLC-2** (Product Specification # 37494)
- Load Share speed control **2301E** (Product Specification # 03404)
- Load Sharing Module **LSM** (Product Specification # 82686)
- **SPM-A** Synchronizer (Product Specification # 82383)
- **Power Generation Learning Module** (Product Specification # 03412): P/N 8447-1012

FEATURES OVERVIEW

CONTACT

North & Central America

Tel.: +1 970 962 7331
 ☎ SalesPGD_NAandCA@woodward.com

South America

Tel.: +55 19 3708 4800
 ☎ SalesPGD_SA@woodward.com

Europe

Tel. Stuttgart: +49 711 78954 510
 Tel. Kempen: +49 2152 145 331
 ☎ SalesPGD_EUROPE@woodward.com

Middle East & Africa

Tel.: +971 2 6275185
 ☎ SalesPGD_MEA@woodward.com

Russia

Tel.: +7 812 319 3007
 ☎ SalesPGD_RUSSIA@woodward.com

China

Tel.: +86 512 8818 5515
 ☎ SalesPGD_CHINA@woodward.com

India

Tel.: +91 124 4399 500
 ☎ SalesPGD_INDIA@woodward.com

ASEAN & Oceania

Tel.: +49 711 78954 510
 ☎ SalesPGD_ASEAN@woodward.com

www.woodward.com

Subject to alterations, errors excepted.

Subject to technical modifications.

This document is distributed for informational purposes only. It is not to be construed as creating or becoming part of any Woodward Company contractual or warranty obligation unless expressly stated in a written sales contract.

We appreciate your comments about the content of our publications. Please send comments including the document number below to
 stgt-doc@woodward.com

© Woodward

All Rights Reserved

For more information contact:

SPM-D2-10 Series		SPM-D2-10 Series							
	Package	-	X	N	XN	PSY5	PSY5...W	YB	NYB
Measuring / Display									
Generator/System A voltage		2-ph	2-ph	2-ph	2-ph	2-ph	2-ph	3/2-ph	3/2-ph
Busbar/System B voltage		2-ph	2-ph	2-ph	2-ph	2-ph	2-ph	3/2-ph	3/2-ph
Control									
Breaker	1	1	1	1	1 or 2	1 or 2	1	1	1
Synchronization	2-ph	2-ph	2-ph	2-ph	2-ph	2-ph	3/2-ph	3/2-ph	3/2-ph
Isolated Operation	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dead bus start functionality ^{#1}	On-demand	On-demand	On-demand	On-demand	Enhanced	Enhanced	Enhanced	Enhanced	Enhanced
Switchable parameter ^{#2}	-	-	-	-	✓	✓	-	-	-
Controller									
Discrete raise/lower: Speed	✓	✓#3	✓	✓#3	✓	✓	✓	✓	✓
Discrete raise/lower: Voltage	✓	✓#3	✓	✓#3	✓	✓	✓	✓	✓
Analog Output: Speed ^{#4}	-	✓	-	✓	-	-	-	-	-
Analog Output: Voltage ^{#4}	-	✓	-	✓	-	-	-	-	-
PWM Output: Speed ^{#5}	-	✓	-	✓	-	-	-	-	-
I/Os									
Discrete alarm inputs	4	4	4	4	4	4	4	5	5
Discrete outputs	2	2	2	2	3	3	3	3	3
Analog outputs: +/- 10 V, +/- 20 mA, PWM; configurable	-	2	-	2	-	-	-	-	-
USB Serial interface	1	1	1	1	1	1	1	1	1
Power Supply									
24 Vdc	✓	✓	-	-	✓	-	✓	-	-
Wide Range: 90 to 250 V _{AC} / 120 to 375 V _{Dc}	-	-	✓	✓	-	✓	-	✓	✓
Accessories									
Configuration via PC (ToolKit)	✓	✓	✓	✓	✓	✓	✓	✓	✓
Listings/Approvals									
UL / cUL Listing (61010, 6200)	✓	✓	✓	✓	✓	✓	✓	✓	✓
CE Marked	✓	✓	✓	✓	✓	✓	✓	✓	✓
Part Numbers									
Measuring inputs 100 Vac:	8440....	...-2166	...-2168	...-2174	...-2172	-	-	...-2167	...-2177
Measuring inputs 400 Vac ^{#6} :	8440....	...-2164	...-2171	...-2175	...-2190	...-2170	...-2173	...-2176	...-2189
Technical Manual	B37615				B37616			B37617	

- #1 Dead bus start functionality
On-Demand: Closing of CB on demand
Enhanced: Black start (closing to de-energized second side of a breaker for following conditions):
 - dead system 1 - live system 2
 - live system 1 - dead system 2
 - dead system 1 - dead system 2
- #2 Switch from Parameter set #A to #B by activating DI #6
- #3 Configurable to either speed or voltage
- #4 Analog bias outputs for voltage and speed freely configurable for all levels (+/-1 V, +/-3 V, 0 to 5 V, 0.5 to 4.5 V, +/-10 V +/-5 V, 0 to 20 mA, +/-20 mA, and much more)
- #5 Speed bias output configurable as 500 Hz PWM output with adjustable voltage level
- #6 All units with 400 V measuring inputs can also be used for 100 V system voltage